



## FEATURES



- Blue thermoplastic elastomer, copolyester construction
- Patented\* latching mechanism adjusts the wristband's diameter from 1.7 to 2.6 inches
- Interior wristband resistance:  $< 1 \times 10^5$  ohms
- Exterior wristband resistance:  $> 1 \times 10^7$  ohms
- Unique dual contact design is to be paired with an [SCS MagSnap 360™ Dual-Wire Coil Cord](#) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- Backplate Material: Stainless-steel
- Compatible with [SCS Dual-Wire Workstation Monitors](#) and other brands that accept a 3.5 mm phono plug.
- Meets requirements of ANSI/ESD S20.20, ANSI/ESD S1.1, EN 61340-5-1 and IEC 61340-4-6
- May be cleaned with water and mild detergent or 10% isopropyl solution

Item	Description
<a href="#">2240</a>	Wristband Only
<a href="#">2241</a>	Wristband with 6' Coil Cord
<a href="#">2242</a>	Wristband with 12' Coil Cord

Unless otherwise noted, tolerance  $\pm 10\%$

Specifications and procedures subject to change without notice.

\*U.S. Patent 6,256,847



Made in the  
United States of America

# SCS

## MAGSNAP 360™ DUAL-WIRE THERMOPLASTIC WRISTBAND

DRAWING  
NUMBER

2240

DATE

January  
2018