
3M[™] Humidity Indicator Cards (HICs) for IPC/JEDEC J-STD-033

IPC/JEDEC will soon release Revision B of the J-STD-033 standard for dry packaging surface mount devices. A new HIC will be required. This 5%, 10%, 60% card will have to meet the requirements of new IPC/JEDEC testing for observability and accuracy. 3M's 51060HIC125 will comply with revision B requirements.

Humidity Indicator Cards (HICs) are printed with moisture sensitive spots which respond to various levels of humidity with a visible color change from blue to pink. The humidity inside dry packed barrier bags can be monitored by including an HIC inside. When the bag is opened, the card can be examined for proper dryness inside the bag. This indicates that the barrier bag and desiccant functioned correctly.



3MTM 51015HIC125

Meets 033 Revision A


This card meets the IPC/JEDEC J-STD-033A standard.

Card Size: 2" x 3" inches Indicates: 5,10,15%

Packing: 125 cards in an air-tight can.

Standards

Complies with IPC/JEDEC J-STD-033A.



3MTM 51060HIC125

Meets 033 Revision B

This card meets the future release of IPC/ JEDEC J-STD-033B standard.

Card Size: 2" x 3" inches Indicates: 5,10,60%

Packing: 125 cards in an air-tight can.

Standards

Complies with future release of IPC/ JEDEC J-STD-033B.

Specifications Typical Values

Materials: Blotting paper impregnated

with cobaltous chloride.

Based on ambient temperature of 75°F. Accuracy: Tolerance: Approx. 2.5% for each 10^oF away from

75°F.

Part Numbers

P/N	DESCRIPTION:
51015HIC125	5, 10,15 Spot Humidity Indicator Card 125/Can
51060HIC125	5, 10,60 Spot Humidity Indicator Card 125/Can

See all the 3M HICs online at www.3M.com/static

4HIC100



HUMIDITY . INDICATOR DESICCANT WARNING Discard if Circle Avoid Minal

3HIC125

6HIC200

СТ D A T Т R О D U S

Humidity Indicator Cards ~ IPC/JEDEC

PRODUCT HIC: 51015 SPOT, 51060 SPOT ITEM NUMBER SEE ABOVE

DATASHEET 7033-A

3M Electronic Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000

US and Canada: 866-722-3736

Fax: 866-722-3735 Intl: 919-718-0000; Fax: 919-774-8174

email: 3Mstaticinfo@mmm.com; www.3M.com/static

3M is a trademark of 3M Company. All other trademarks herein are the property

of their respective owners.