

### TECHNICAL DATA



### Features

- Locates leaks generated by pressure, vacuum, water, gas or air
- LED bargraph display leakage level
- Audible sound assists in pinpointing leak
- Earphone jack for loud environments (earphones sold separately)
- User adjustable sensitivity wheel
- Battery check button
- 20 to 100 kHz frequency response
- Ultrasonic Transmitter sends a 40 kHz signal which, when detected by the meter, indicates the location and magnitude of a leak (GS-400, sold separately)
- Includes rubber bottle plug with plastic tubing, 1/2" PVC pipe assembly, hard carrying case

### Specifications

Frequency Response:	20 to 100 KHz
Sensitivity Adjustment:	Yes (wheel)
Display:	LED Bargraph
Alarm:	Audible (buzzer)
Earphone Jack:	Yes
Power Supply:	9V Battery
Low Battery Indicator:	Yes
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity:	10-90%
Dimensions:	10 x 2.8 x 1.1" (255 x 70 x 28mm)
Weight:	5.3 oz (260g)

Model	Description
GS-5800	Ultrasonic Leak Detector
GS-400	Ultrasonic Transmitter
CA-05A	Soft Carrying Case