Temperature & Humidity Meter, Compact Series Model R1910



Features

• Measures ambient temperature and relative humidity

- Designed for one-handed operation
- Backlit dual LCD display
- User selectable °F/°C
- Max, min and data hold functions
- Low battery indicator and auto shut off
- Includes batteries

TECHNICAL DATA

Specifications

Temperature

Measuring Range: Accuracy: Resolution:

Humidity

Measuring Range: Accuracy: Resolution:

General Specifications

Display: Backlit Display: Data Hold: Max: Min: Sampling Rate: Overange Indicator: Auto Shut-off: Low Battery Indicator: Power Supply: Product Certifications: Operating Temperature: Storage Temperature: Operating Humidity Range: Dimensions: 14 to 140°F (-10 to 60°C) ±2.0°F (1.0°C) 0.1°F/°C

0 to 100% RH ±5% RH 0.1% RH

Dual LCD Yes Yes Yes Yes 1 time/second Yes Yes (after 5 minutes, off) Yes 3 "AAA" Batteries CE 32 to 122°F (O to 50°C) 14 to 140°F (-10 to 60°C) 10 to 80% 6.3 x 2 x 1.1" (155 x 50 x 28mm) 4.2oz (102g)

Weight:

Model	Description
R1910	Temperature & Humidity Meter, Compact Series
CA-52A	Soft Carrying Case



Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com