



### TECHNICAL DATA

#### Specifications

##### Leak Detector (Receiver)

Frequency Response: 40 kHz  $\pm$ 2 kHz  
 Sensitivity Adjustment: Yes (wheel)  
 Alarm: Audible (Ticking) / Visual (LED)  
 Earphone Jack: Yes (Earphones included)

##### Transmitter

Output Frequency: 40 kHz  
 Power Indicator: LED

##### General Specifications

Power Supply: 2 "9V" Batteries  
 Product Certifications: CE, RoHS  
 Operating Temperature: 32 to 104°F (0 to 40°C)  
 Storage Temperature: -4 to 122°F (-20 to 50°C)  
 Dimensions:

Receiver: 7.6 x 2 x 1.2"  
 (192 x 50 x 30 mm)  
 Transmitter: 3.9 x 2.3 x 1.1"  
 (101 x 59 x 28 mm)

##### Weight:

Receiver: 4.1 oz (115 g)  
 Transmitter: 3.2 oz (90 g)



#### Features

- Locates leaks generated by pressure, vacuum, water, gas or air
- Visible (LED) and Audible (ticking) alarms assist in pinpointing leaks
- Earphone jack for loud environments (earphones included)
- User adjustable sensitivity wheel
- Ultrasonic Transmitter generates a 40 kHz signal
- Includes transmitter, earphones, carrying case and batteries

Model	Description
R9100	Ultrasonic Leak Detector